

SAFETY DATA SHEET

according to 1907/2006 EC, Article 31

Page 1 of 3

SYLFAT™2

Revision 3
Revision date 16-Mar-2011

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name SYLFAT™2
Company Arizona Chemical B.V.
P.O. Box 60053
NL-1320
AB ALMERE
The Netherlands
regulatory.eu@azchem.com
Telephone +31 36 54 62 800
Fax +31 36 54 62 957
Emergency telephone number +44 1865 407 333
Product code 2791E

2. HAZARDS IDENTIFICATION

Main hazards No Significant Hazard.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Tall Oil Fatty Acid	100%	61790-12-3	263-107-3	

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Contact lenses should be removed. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation May cause irritation to mucous membranes. Move the exposed person to fresh air.

Ingestion May cause irritation to respiratory system. Ingestion may cause nausea and vomiting. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing media Use extinguishing media appropriate to the surrounding fire conditions. Use as appropriate: carbon dioxide (CO2). Foam. Water spray.

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Wear suitable respiratory equipment when necessary.

SYLFAT™2Revision 3
Revision date 16-Mar-2011**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Keep away from heat. Keep away from sources of ignition - No smoking.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Keep away from heat. Keep away from sources of ignition - No smoking. Keep away from direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	In case of splashing, wear: Approved safety goggles.
Protective equipment	Wear protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Yellow.
Odour	Mild.
Boiling point	>200°C
Flash point	200°C
Vapour pressure	3 mbar @ 150°C
Relative density	905 kg/m ³ @ 20°C
Water solubility	immiscible in water.
Partition coefficient	4.9-6.0
Melting point	-6°C

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Direct sunlight. Heat.
Materials to avoid	Oxidising agents.

