



SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Arizona Chemical Company  
P.O. Box 550850  
Jacksonville, FL 32255

24 Hour Emergency Assistance:  
Chemtrec: 800/424-9300  
Other Information: 800/733-1374

Product Name: SYLVACOTE® 7118  
Chemical Identity: Trade Secret  
Generic Name: Maleic Modified Rosin Resin  
Chemical Family: Rosin Based Resins  
CAS Number: Confidential (See Section 15).

SECTION 2 COMPOSITION/INFORMATION OF INGREDIENTS

	ACGIH TLV (mg/m <sup>3</sup> )		OSHA PEL (mg/m <sup>3</sup> )	
	TWA	STEL	TWA	STEL
Particulates not otherwise classified	10	NE	NE	NE
Particulates not otherwise regulated				
Total dust	NE	NE	15	NE
Respirable fraction	NE	NE	5	NE

TLV = Threshold Limit Value  
PEL = Permissible Exposure Limit  
TWA = Time-weighted average (8 hours)  
STEL= Short term (15 minute) exposure limit  
NE = Not established

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Amber solid with a mild odor.

1. WARNING! MAY FORM FLAMMABLE OR EXPLOSIVE DUST-AIR MIXTURES.
2. AVOID BREATHING DUST.

POTENTIAL HEALTH EFFECTS:

EYE: Resin dust can cause mechanical irritation.

SKIN: No effects are known from the solid resin or dust.

=====  
**SECTION 3 HAZARDS IDENTIFICATION CONT'D**  
=====

INHALATION: During normal use of the molten resin at temperatures below 180 °C (356°F) there is only minimal risk from inhalation of resin fumes, when effective ventilation is used. Inhalation of resin dust or fumes may cause mild irritation of the nose and throat in sensitive individuals.

INGESTION: Not a probable route of entry into the body.

SUBCHRONIC EFFECTS (Target Organ Effects): No effects known.

CHRONIC EFFECTS: No effects known.

=====  
**SECTION 4 FIRST AID MEASURES**  
=====

EYE CONTACT: In case of contact, immediately flush eyes with plenty of water. Call a physician if signs of irritation appear.

SKIN CONTACT:

Solid Resin: As good industrial hygiene practice, at the end of each work shift, wash skin with plenty of soap and water. If resin contacts clothing, wash before reuse.

Molten Resin: Cool the affected area with cold water, but do not attempt to remove the solidified resin from the skin. Consult a physician immediately for burn treatment.

INHALATION: Remove to fresh air if effects occur from inhalation of molten resin vapor or fumes, or resin dust.

INGESTION: Emergency care should not be needed.

=====  
**SECTION 5 FIRE FIGHTING MEASURES**  
=====

Flash point: >201 °F (93.89 °C)

Upper/lower flammable limits: Unknown

Autoignition temperature: Unknown

Flammability classification: Non-hazardous

Flame propagation rate: Not applicable

Extinguishing media: Water fog, foam, carbon dioxide or dry chemical.

Special precautions: Toxic gases such as carbon monoxide may be released during fire. Use positive-pressure, self-contained breathing apparatus and full protective clothing.

Unusual Fire and Explosion Hazards: May form flammable dust-air mixtures. See Engineering Controls (page 3).

=====  
**SECTION 6 ACCIDENTAL RELEASE MEASURES**  
=====

In a clean area, recover for reuse. Dispose of contaminated material.

=====  
**SECTION 7 HANDLING AND STORAGE**  
=====

When handling molten resin, use adequate ventilation to avoid the accumulation of fumes. Use good housekeeping to prevent dust accumulation.

=====  
**SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION**  
=====**EYES:**

Solid Resin: Use safety glasses. An eye wash is recommended.

Molten Resin: Use chemical safety goggles. An eye wash is recommended.

**SKIN:**

Solid Resin: As good industrial hygiene practice, impervious (for example, nitrile) gloves are recommended.

Molten Resin: Heat-resistant gloves and other protective clothing should be worn to prevent body contact. A safety shower is recommended.

**INHALATION:**

Solid Resin: For normal operations, no respiratory protection is required. A dust mask is recommended if resin dust becomes airborne.

Molten Resin: An air purifying respirator designed for organic vapors should provide adequate protection.

**ENGINEERING CONTROLS:** Use adequate ventilation. In process operations capable of generating static electricity and/or dust clouds; grounding, venting, and explosion relief provisions must be used.

=====  
**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**  
=====

Appearance/state: Amber solid  
Odor: Mild  
Ph: Not applicable  
Vapor Pressure: <0.001 mm Hg at 20°C (68°F)  
Vapor density: Not applicable  
Boiling point: Not applicable  
Melting point: 120°C  
Solubility in water: <0.1% at 25°C (77°F)  
Specific gravity: >1 at 25°C/25°C (water=1.00)  
Evaporation rate: Approx. 0 (n-BuAc=1)  
% Volatile by weight: 0

=====  
**SECTION 10 STABILITY AND REACTIVITY**  
=====

Chemical stability: Stable under normal temperatures and pressures.

Conditions to avoid: Formation of dust clouds. This product is not reactive with water.

Chemicals to avoid: None known.

Hazardous Polymerization: Will not occur under normal temperatures and pressures.

Hazardous Decomposition Products: Thermal decomposition products include toxic oxides of carbon.

=====  
**SECTION 11 TOXICOLOGICAL INFORMATION**  
=====

The total product is not on the International Agency for Research on Cancer (IARC) or National Toxicology Program (NTP) or OSHA lists of carcinogens or potential carcinogens.

TOXICITY DATA: The following data on test animals indicate that chemically similar products have low acute toxicity potential and are not skin or eye irritants by OSHA criteria.

ROUTE-SPECIES	TEST	DOSAGE	UNITS	IRRITATION DATA
Oral-rat	LD50	>5	g/kg	Skin-rabbit Non-irritant Eye-rabbit Mild irritant

OTHER: Molten resin can cause thermal burns.

=====  
**SECTION 12 ECOLOGICAL INFORMATION**  
=====

There is no data available for this product.

=====  
**SECTION 13 DISPOSAL CONSIDERATIONS**  
=====

Dispose of waste by landfill or incineration in accordance with all local, state and federal regulations.

Resource Conservation and Recovery Act (RCRA): This product is not included in the lists of hazardous substances (40 CFR 261.33), nor does it exhibit the characteristics of hazardous waste (40 CFR 261.20-24).

=====  
**SECTION 14 TRANSPORT INFORMATION**  
=====

DOT - Department of Transportation Hazardous Materials Regulations

DOT Hazard Class: Not applicable  
DOT Proper Shipping Name: Not applicable  
Technical Name: Not applicable  
DOT Identification Number: Not applicable  
Surface Freight Classification: Plastic Synthetic

=====  
**SECTION 15 REGULATORY INFORMATION**  
=====

Toxic Substances Control Act (TSCA): This product is on the TSCA Inventory.

SARA, Title III, Section 313 (40 CFR 372): This product contains the following substances which are reportable under SARA Toxic Chemical Release Reporting Regulations:

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt%</u>
None		

SARA 311/312 Hazard Categories: This product has the following hazard categories: None.

New Jersey Worker and Community Right To Know Act: This product contains the following top five substances:

<u>Chemical Name</u>	<u>CAS or NJTS #</u>	<u>Wt%</u>
Confidential	NJT SRN-6782	100

Pennsylvania Worker and Community Right To Know Act: This product contains the following substances which appear on the Hazardous Substance List:

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt%</u>
None		

WHMIS (Canada) Status: Not a controlled product under WHMIS.

International Inventory Status: This product is either listed or exempt from listing on the following inventories: Canada DSL, Europe EINECS, Japan ENCS, Korea ECL, Australia AICS, China IECS, Philippines PICCS.

=====  
**SECTION 16 OTHER INFORMATION**  
=====

**Hazard Ratings:** NFPA 1 Health 1 Fire 0 Reactivity

**Revision Note:** Revision 10. Revised Sections 1 and 15.

**Prepared by:** L. M. Krzywanska

**Title:** Product Regulatory Technologist.

The information contained herein is based on data believed to be reliable, but is furnished without warranty or guaranty of any kind, and Arizona Chemical Company disclaims any liability incurred from the use or reliance upon the same.

END OF MSDS