



Product Data Sheet

SYLVAMELT[®] 401

SYLVAMELT[®] 401 is a blend of tall oil rosin derived tackifier components, designed as replacement of tackified mixtures used for low VOC flooring adhesives.

FEATURES

- Low volatility

APPLICATIONS

- Low VOC Flooring Adhesives

PROPERTIES	SPECIFICATIONS
Colour, Gardner 63, 1:1 in toluene	7 max
Acid number, mg KOH/g	60-80
Viscosity at 60°C, mPas	2000-3000
	TYPICAL
Softening Point, Ring & Ball, °C	Semi-liquid
Viscosity at 70°C, mPas	7000
Viscosity at 75°C, mPas	6000

SOLUBILITY	SYLVAMELT [®] 401 is soluble in most common organic solvents and insoluble in water
COMPATIBILITY	SYLVAMELT [®] 401 is compatible with most commonly used Acrylics and PVAc-copolymers
DELIVERY FORM	SYLVAMELT [®] 401 is available in 200 kg open head steel drums or bulk.
FDA STATUS	SYLVAMELT [®] 401 meets the requirements of the Code of Federal Regulations, Title 21 under the sections 175.105 Adhesives
CN CODE	3806.30 00



Arizona Chemical, PO Box 60053, 1320 AB Almere, The Netherlands
Telephone +31 36 546 2800 Telefax +31 36 546 2811 Web www.arizonachemical.com

Revision July 2009

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification.