



# Product Data Sheet

Revision Date: September 2009

## AQUATAC® 9027

**AQUATAC 9027®** is a high-solids solution of rosin-based tackifiers, formulated with a low softening point for product assembly and pressure sensitive adhesive applications. **AQUATAC® 9027** can be used as the sole tackifier for low temperature applications or difficult to bond substrates.

PROPERTIES*	TYPICAL	SPECIFICATIONS
Solids Content, %	90	89.0 – 91.0
Viscosity, RVT Brookfield, spindle #7, 20 rpm, 30 °C, cps	160,000	
pH	9	8.0 – 10.0
Base Resin Softening Point	27	

<b>Shipping Data:</b>	<b>AQUATAC® 9027</b> is available in liquid in 50-gallon drums, net 420 lb. and bulk.
<b>Food and Drug Administration Coverage</b>	<b>AQUATAC® 9027</b> meets the ingredient requirements of the following section of the Code of Federal Regulations, Title 21 when used according to the regulations and any limitations that may apply:  <b>175.105 Adhesives</b>

\*Arizona Chemical Test Methods available on request



**Technical Service: Savannah, GA (912) 238-6556**  
**Sales Service: Jacksonville, FL - (800) 733-1374**

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.