



# Product Data Sheet

Revision Date: 10/07

## SYLVABLEND<sup>®</sup> SC100

**SYLVABLEND<sup>®</sup> SC100** is a blend of tall oils and distillates designed to perform in applications that require a specialty formulation with less inherent variability than crude tall oil. Typical uses include chemical intermediates or precursors to corrosion inhibitors, floatation reagents, emulsifiers, and soaps.

PROPERTIES	TYPICAL	SPECIFICATIONS
Acid Value	155	145 - 165
Pour Point, °C (°F)	-20 (-4)	-10 (14) Maximum
Composition:		
Moisture, %	0.6	1.5 Maximum
Rosin Acids, %	21	15 -25
Fatty Acids Total, %	59	
Specific Gravity, 25°/25°C	0.93	
Weight Per Gallon, 25°C, lb.	7.8	
Viscosity, CPS @ 25°C	220	
Flash Point, Closed Cup, °F	>200	

<b>Dot Shipping Classification:</b>	Non hazardous
<b>Available Forms/Packaging:</b>	Available in tank car, tank truck



**Technical Service: Savannah, GA (912) 238-6556**  
**Sales Service: Jacksonville, FL - (800) 733-1374**

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.