



# Product Data Sheet

Revision Date: 12/13/2010

## SYLVAROS™ NCY

### TALL OIL ROSIN

**MAJOR USES:** Paper size. Rubber chemicals, Resins for inks, coatings and adhesives.

PROPERTIES	TYPICAL	SPECIFICATIONS
Appearance at 25°C	Yellow solid	
Rosin Acids <sup>(1)</sup> , %	84.0	
Fatty Acids	3.4	4.0 Maximum
Unsaponifiables	5.0	
Acid Number	163	162 Minimum
Softening Point, Ring & Ball, °C	75	
Ash, %	<0.1	
Gardner Color, neat	7+	8.0 Maximum
Specific Gravity, 25°C/25°C	1.05	
Flash Point, °C	221 (430°F)	

<b>Shipping Data:</b>	Molten in lined insulated tank cars and stainless steel tank trucks, and solid in 57-gallon galvanized steel rosin drums (496 lbs. net).
<b>DOT Shipping Classification:</b>	Non-hazardous.

<sup>(1)</sup>AQCM 010



**Technical Service: Savannah, GA (912) 238-6556**  
**Sales Service: Jacksonville, FL - (800) 733-1374**

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.