



# Product Data Sheet

Revision Date: 01/2011

## SYLFAT™ DP-8

### PITCH

**SYLFAT™ DP-8** is a residual pitch product. It is a dark tar-like material that liquefies upon warming to 70°C (158°F).

**Major uses include:** rubber reclaiming tackifiers, limed pitch for asphalt tile, roofing compounds, inks, oil well drilling fluid additives, flotation reagents, varnishes, alkyd and phenolic resins

COMPOSITION, PERCENT	TYPICAL	SPECIFICATIONS
Fatty Acids and Esterified Acids	25	
Rosin Acids	25	
Unsaponifiabiles	7	
<b>PROPERTIES</b>		
Appearance at 25°C	Dark soft solid	
Acid Number	110	
Moisture %	0.5	0.8
Ash, %	0.6	
Specific Gravity, 25°C/25°C	0.97	
Viscosity, SSF @ 99°C (210°F)	50	
Flash Point	(430°F)	
Iodine Value	18	

<b>Shipping Data:</b>	<ul style="list-style-type: none"> <li>Molten in insulated tank cars and stainless steel tank trucks.</li> </ul>
<b>DOT Shipping Classification:</b>	<ul style="list-style-type: none"> <li>Non-hazardous.</li> </ul>
<b>FDA Warning:</b>	<ul style="list-style-type: none"> <li>This product does not meet FDA requirements for use in animal feed.</li> </ul>



**Technical Service: Savannah, GA (912) 238-6556**  
**Sales Service: Jacksonville, FL - (800) 733-1374**

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.