



Product Data Sheet

Revision Date: 03/04

UNI-REZ® 2940 POLYAMIDE RESIN

UNI-REZ® 2940 POLYAMIDE RESIN is a cosolvent type polyamide resin which is soluble in mixtures of aliphatic hydrocarbons and alcohols. **UNI-REZ® 2940 POLYAMIDE RESIN** provides fast solvent release and good grease resistance in flexographic inks for plastic substrates.

TYPICAL PROPERTIES

Softening Point, Ring & Ball, °C	110
Color, 50% in n-Propanol, Gardner	6
Viscosity, Brookfield, cps at 160°C	1500
Viscosity, 50% in Isopropanol/Toluene, (1:1 by weight), 25°C, Gardner	P
Acid Number	2
Amine Number	3
Flash Point, °C	271
Pounds per Gallon, 25°C	8.2

FDA Status:	UNI-REZ® 2940 POLYAMIDE RESIN meets the requirements of the Code of Federal Regulations, Title 21, under the following sections: 175.105 Adhesives 175.300 Resinous and Polymeric Coatings 175.320 Resinous and Polymeric Coatings for Polyolefin Films 177.1200 Cellophane
DOT Shipping Classification:	Non-hazardous.
Shipping:	Granulated resin, packaged in multiwall paper bags, 50 lbs. net.
Storage:	Granulated forms of resin are prone to slow oxidation which may result in darkening and/or have an adverse effect on solubility after prolonged storage. The shelf life of this product can be extended by storing in full, closed containers kept in a cool, dry area.



Technical Service: Savannah, GA (912) 238-6556
Sales Service: Jacksonville, FL - (800) 733-1374

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.